

www.raisecom.com

Mirror Function Commands-3



CONTENTS



Chapter 1 Mirror Commands ----- 1

 1.1 mirror source-port-list ingress *port-list* egress *port-list* -----1

Chapter 1 Mirror Commands

1.1 mirror source-port-list ingress *port-list* egress *port-list*

[Function]

Set source port and mirror rule of mirror function, use “no” command to perform deletion.

[Command Format]

mirror source-port-list ingress *port-list* egress *port-list*

[Parameter]

source-port-list: source mirror port;

port-list: physical port number, range from 1-26, use ‘,’ and ‘-’ to input multi ports ;

ingress: ingress mirror divider;

egress: egress mirror divider;

both: mirror both ingress and mirror egress packets;

all: all the mirror configuration

[Default]

No source mirror port is set by default.

[Command Modes]

Global configuration mode, Privileged user

[Command Executing Instruction]

Only users whose priority is 15 can perform the command.

[Explanation of command execution echo]

The port list is wrong!

Error occurred when input multi ports using “-“ and “,”.

The port X has been set to be monitor port , please reset!

The port X is already a monitoring port.

Set successfully !

[Example]

Set physical port of 1 to 5 is mirror port and mirror rule is ingress:

Raisecom(config)# **mirror source-port-list ingress 1-5**

Delete source mirror of port:

Raisecom(config)# **no mirror source-port-list**

Delete all mirror setting:

Raisecom(config)# **no mirror** *all*

[Related commands]

Commands	Description
show mirror	Show the setting of mirror function.



北京瑞斯康达科技发展有限公司
RAISECOM TECHNOLOGY CO.,LTD.

Address: 2nd Floor, South Building of Rainbow Plaza, No.11 Shangdi Information Road,
Haidian District, Beijing Postcode: 100085 Tel: +86-10-82883305 Fax: +86-10-82883056
Email: export@raisecom.com <http://www.raisecom.com>